XYZ-40G 2.2 KW Thin Oil Station Thin Oil Lubrication System 63L/Min

## **Basic Information**

. Place of Origin: Shanghai YIKU . Brand Name: XYZ-40G Model Number: Minimum Order Quantity: 1 piece • Price: negotiable Packaging Details: Wooden box . Delivery Time: 2-3 weeks • Payment Terms: L/C, T/T • Supply Ability: 10 units/month



## **Product Specification**

Fuel Tank Capacity: 1 M3
Nominal Flow Rate: 63 L/min
Oil Pump Power: 2.2 KW
Fuel Supply Temperature: 40±3
Filter Area: 0.19m3
Weight: 824kg

• Highlight: 2.2 KW Thin Oil Station,

 ${\bf 2.2~KW~Thin~Oil~Lubrication~System}, \\$ 

Thin Oil Station 63L/Min

## **Product Description**

XYZ-40G Thin oil station

本品 用于稀油循 滑系 中,其工作介 汽 机油,20-25号机械油及 机油, 粘度等 N22-N460.

稀油站的公称供油 力 0.63MPa,精度0.08-0.12mm,冷却水温≤28 ,冷却水 力0.2-0.3MPa,器 油温度 50 ,温降7-8 ,使用蒸汽加 蒸 汽力 0.2-0.4MPa.

油站由油箱,油 装置,油器,冷却器,表,管道和 等成,整体式

This product is suitable for thin oil circulation lubrication system, its working medium is turbine oil, 20-25 mechanical oil and rolling oil, kinematic viscosity class is N22-N460.

The nominal oil supply pressure of the thin oil station is 0.63MPa, the filtration accuracy is 0.08-0.12mm, the cooling water temperature is ≤28 ° C, the cooling water pressure is 0.2-0.3MPa, the oil inlet temperature of the heat exchanger is 50 ° C, the temperature drops 7-8 °C, and the steam pressure is 0.2-0.4MPa when using steam heating.

The oil station is composed of fuel tank, oil pump device, oil filter, cooler, instrument, pipeline and valve, etc. The structure is integrated

## 上海依库机电设备 Shanghai YIKU Power Equipment Co., Ltd

8613916002258



657925203@qq.com



axialfanparts.com

5587 Dongchuan Road, Pudong New Area, Shanghai